29 142

GROHTHERM® SMARTCONTROL

TRIPLE FUNCTION THERMOSTATIC VALVE TRIM WITH CONTROL MODULE



STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE SmartControl®: push for ON-OFF, turn for volume adjustment from $\mathsf{EcoJoy}^\mathsf{TM}$ to Full Flow, exchangeable symbols
- GROHE TurboStat® compact 3/4" cartridge with wax thermo element
- GROHE SafeStop safety button with manual override at 100°F/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- · Multiple outlets can be run simultaneously
- 6 1/4" Metal wall escutcheon with GROHE QuickFix®
- 3/8" Thin profile escutcheon
- Wall plate is angle adjustable up to 6°
- · Optional flow reducer for CALGreen compliance included (Note: Cannot be used for shower systems that include tub spout)
- · Built-in check valve with dirt strainer
- Includes icons to customize push buttons: Hand Shower, Showerhead, Bath Filler, Showerhead (2nd Spray), Showerhead (3rd Spray) & Body Spray
- Includes service stops
- Maximum combined flow performance: 9.5gpm (36L/min) @ 43.5psi (3 bar)
- Requires Grohtherm® Rapido® SmartBox (35 601) (sold separately)

PRODUCT FEATURES:

- GROHE StarLight®
- GROHE TurboStat®
- GROHE QuickFix®
- SafeStopPlus

CERTIFICATIONS:

- · Massachusetts Plumbing Board Approved
- ASSE 1016
- CSA B125.1
- CSA B125.16
- ASME A112.18.1
- ASME A112.1016



AVAILABLE FINISHES:

29142000



NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.



29 142

GROHTHERM® SMARTCONTROL



TRIPLE FUNCTION THERMOSTATIC VALVE TRIM WITH CONTROL MODULE

TECHNICAL DATA:

Product Height 6-1/4 in

Product Length 1-11/16 in

Product Width 6-1/4 in

